



**CU4-1800**
Gasdruckfeder

Grün
Blau
Rot
Gelb
Schwarz

**T: < 80 °C** $S = \text{Hub}$

S	L ± 0.25	L min	F1 [daN]	F2 [daN]	m [kg]	V [L]	Order No.
6	66	60	1800	2400	0.60	0.030	CU4-1800-6
10	80	70	1800	2500	0.66	0.044	CU4-1800-10
16	106	90	1800	2500	0.79	0.072	CU4-1800-16
25	135	110	1800	2600	0.93	0.100	CU4-1800-25
32	162	130	1800	2600	1.06	0.126	CU4-1800-32
40	190	150	1800	2600	1.19	0.150	CU4-1800-40
50	220	170	1800	2700	1.32	0.179	CU4-1800-50
65	271	206	1800	2800	1.52	0.24	CU4-1800-65

EINBAUVARIANTEN

Druckmedium	N2
Max. Fülldruck (bei 20° C)	150 bar
Min. Fülldruck (bei 20° C)	25 bar
Betriebstemperatur	0° C - 80° C
Temperaturabhängige Druckerhöhung	0,3% / 1° C
Max. Kolbengeschwindigkeit	0,8 m/s
Empfohlene max Hübe / min (bei 20° C)	~ 100
Instandhaltungsset	3024836