


**CU4-2900**
Gasdruckfeder

8

Grün
Blau
Rot
Gelb
Schwarz




T: < 80 °C

 $S = \text{Hub}$

S	L ± 0.25	L min	F1 [daN]	F2 [daN]	m [kg]	V [L]	Order No.
10	85	75	2950	4000	1.14	0.08	CU4-2900-10
16	103	87	2950	4200	1.28	0.12	CU4-2900-16
25	130	105	2950	4500	1.49	0.16	CU4-2900-25
32	150	118	2950	4620	1.64	0.20	CU4-2900-32
40	175	135	2950	4720	1.83	0.24	CU4-2900-40
50	205	155	2950	4500	2.06	0.29	CU4-2900-50
65	256	191	2950	4700	2.39	0.35	CU4-2900-65

EINBAUVARIANTEN



Druckmedium	N2
Max. Fülldruck (bei 20° C)	150 bar
Min. Fülldruck (bei 20° C)	25 bar
Betriebstemperatur	0° C - 80° C
Temperaturabhängige Druckerhöhung	0,3% / 1° C
Max. Kolbengeschwindigkeit	0,8 m/s
Empfohlene max Hübe / min (bei 20° C)	~ 80 - 100
Instandhaltungsset	3024837